



H-Shield NB

Packaging & Weight Chart

SIZE	FOAM	LTRR	PCS	LBS/PC	LBS/SF	LBS/PAL
7/16 OSB						
1.5	1.0	6.3	32	52.70	1.647	1686.4
2.0	1.5	9.2	24	55.30	1.728	1327.2
2.5	2.0	12.0	19	57.90	1.809	1100.1
3.0	2.5	15.0	16	60.50	1.891	968.0
3.5	3.0	18.0	13	63.10	1.972	820.3
4.0	3.5	21.1	12	65.70	2.053	788.4

5/8 OSB						
1.6	1.0	6.3	30	66.70	2.084	2001.0
2.1	1.5	9.2	22	69.30	2.166	1524.6
2.6	2.0	12.0	18	71.90	2.247	1294.2
3.1	2.5	15.0	15	74.50	2.328	1117.5
3.6	3.0	18.0	13	77.10	2.409	1002.3
4.1	3.5	21.1	11	79.70	2.491	876.7

5/8 PLY						
1.6	1.0	6.3	30	59.20	1.850	1776.0
2.1	1.5	9.2	22	61.80	1.931	1359.6
2.6	2.0	12.0	18	64.40	2.013	1159.2
3.1	2.5	15.0	15	67.00	2.094	1005.0
3.6	3.0	18.0	13	69.60	2.175	904.8
4.1	3.5	21.1	11	72.20	2.256	794.2

3/4 PLY						
1.7	1.0	6.3	28	69.20	2.163	1937.6
2.2	1.5	9.2	21	71.80	2.244	1507.8
2.7	2.0	12.0	17	74.40	2.325	1264.8
3.2	2.5	15.0	15	77.00	2.406	1155.0
3.7	3.0	18.0	12	79.60	2.488	955.2
4.2	3.5	21.1	11	82.20	2.569	904.2

H-SHIELD NB IS ONLY MANUFACTURED IN THE SIZES LISTED IN THE CHART ABOVE. R-VALUES OTHER THAN THOSE LISTED ABOVE CAN BE ACHIEVED BY INSTALLING A MULTI LAYER SYSTEM CONSISTING OF AN ADDITIONAL LAYER OF FLAT POLYISO UNDER H-SHIELD NB.

HUNTER
Energy Smart Polyiso

888-746-1114 • WWW.HUNTERPANELS.COM