



HUNTER
CONTINUOUS INSULATION

Hunter Panels Xci

Packaging & Weight Chart

	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
Xci FOIL	1.0	6.5	48	6.37	305.66	1536	36864	0.200
	1.5	10.0	32	9.02	288.77	1024	24576	0.280
	2.0	13.3	24	11.71	281.09	768	18432	0.370
	2.5	17.0	19	14.37	272.99	608	14592	0.450
	3.0	20.3	16	17.02	272.38	512	12288	0.530
	3.5	24.0	13	19.71	256.26	416	9984	0.620
	4.0	27.0	12	22.37	268.42	384	9216	0.700
Xci FOIL (CLASS A)	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
Xci 286	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
Xci CG	1.0	6.0	48	12.24	587.47	1536	36864	0.380
	1.5	9.0	32	15.03	480.90	1024	24576	0.470
	2.0	12.1	24	17.85	428.40	768	18432	0.560
	2.5	15.3	19	20.64	392.14	608	14592	0.640
	3.0	18.5	16	23.43	374.85	512	12288	0.730
	3.5	21.7	13	26.25	341.25	416	9984	0.820
	4.0	25.0	12	29.04	348.47	384	9216	0.910
Xci CG (CLASS A)	1.0	6.0	48	12.50	600.00	1536	36864	0.391
	1.5	9.0	32	15.35	491.20	1024	24576	0.480
	2.0	12.1	24	18.20	436.80	768	18432	0.569
	2.5	15.3	19	20.75	394.25	608	14592	0.648
	3.0	18.5	16	23.30	372.80	512	12288	0.728
	3.5	21.7	13	26.15	339.95	416	9984	0.817
	4.0	25.0	12	29.00	348.00	384	9216	0.906
Xci CONCAST	1.0	6.5	48	6.00	312.00	1536	36864	0.190
	1.5	10.0	32	8.00	279.00	1024	24576	0.250
	2.0	13.3	24	11.00	270.00	768	18432	0.340
	2.5	17.0	19	13.30	252.70	608	14592	0.420
	3.0	20.3	16	16.00	255.00	512	12288	0.500
	3.5	24.0	13	16.87	219.30	416	9984	0.527



HUNTER
CONTINUOUS INSULATION

Hunter Panels Xci

Packaging & Weight Chart

	SIZE	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
Xci NB - 7/16" OSB	1.5	1.0	6.6	32	60.24	1927.7	1024	24576	1.880
	2.0	1.5	9.6	24	63.03	1512.7	768	18432	1.970
	2.5	2.0	12.7	19	65.85	1251.2	608	14592	2.060
	3.0	2.5	15.9	16	68.64	1098.2	512	12288	2.140
	3.5	3.0	19.1	13	71.43	928.6	416	9984	2.230
	4.0	3.5	22.3	12	74.25	891.0	384	9216	2.320
	4.5	4.0	25.6	10	77.04	770.4	320	7680	2.410
Xci NB - 5/8" OSB	1.6	1.0	6.6	30	77.24	2317.2	960	23040	2.411
	2.1	1.5	9.6	22	80.03	1760.7	704	16896	2.501
	2.6	2.0	12.7	18	82.85	1491.3	576	13824	2.591
	3.1	2.5	15.9	15	85.64	1284.6	480	11520	2.671
	3.6	3.0	19.1	13	88.48	1150.2	416	9984	2.761
	4.0	3.4	22.3	11	91.25	1003.8	352	8448	2.851
	4.6	4.0	25.6	10	94.04	940.4	320	7680	2.941
Xci NB - 5/8" PLY	1.6	1.0	6.6	30	67.24	2017.2	960	23040	2.101
	2.1	1.5	9.6	22	70.03	1540.7	704	16896	2.188
	2.6	2.0	12.7	18	72.85	1311.3	576	13824	2.277
	3.1	2.5	15.9	15	75.64	1134.6	480	11520	2.364
	3.6	3.0	19.1	13	78.43	1019.6	416	9984	2.451
	4.1	3.5	22.3	11	81.25	893.8	352	8448	2.539
	4.6	4.0	25.6	10	84.04	940.4	320	7680	2.626
Xci NB - 3/4" PLY	1.7	1.0	6.6	28	77.24	2162.7	896	17920*	2.411
	2.2	1.5	9.6	21	80.03	1680.6	672	16128	2.501
	2.7	2.0	12.7	17	82.85	1408.5	544	13056	2.591
	3.2	2.5	15.9	15	85.64	1284.6	480	11520	2.671
	3.7	3.0	19.1	12	88.43	1061.2	384	9216	2.761
	4.2	3.5	22.3	11	91.25	1003.8	352	8448	2.851
	4.7	4.0	25.6	10	94.04	940.4	320	7680	2.941
Xci PLY - 5/8" FT PLY	1.6	1.0	6.6	30	77.24	2317.2	960	19200*	2.411
	2.1	1.5	9.6	22	80.03	1760.7	704	16896	2.501
	2.6	2.0	12.7	18	82.85	1491.3	576	13824	2.591
	3.1	2.5	15.9	15	85.64	1284.6	480	11520	2.671
	3.6	3.0	19.1	13	88.43	1149.6	416	9984	2.761
	4.1	3.5	22.3	11	91.25	1003.8	352	8448	2.851
	4.6	4.0	25.6	10	94.04	940.4	320	7680	2.941
Xci PLY (CLASS A) - 5/8" FT PLY	1.6	1.0	6.6	30	77.50	2325.00	960	19200*	2.422
	2.1	1.5	9.6	22	80.35	1767.70	704	16896	2.511
	2.6	2.0	12.7	18	83.20	1497.60	576	13824	2.600
	3.1	2.5	15.9	15	85.75	1286.25	480	11520	2.679
	3.6	3.0	19.1	13	88.30	1147.90	416	9984	2.759
	4.1	3.5	22.3	11	91.15	1002.65	352	8448	2.848
	4.6	4.0	25.6	10	94.00	940.00	320	7680	2.937
Xci PLY - 3/4" FT PLY	1.7	1.0	6.6	28	87.24	2442.7	896	17920*	2.726
	2.2	1.5	9.6	21	90.03	1890.6	672	13440*	2.813
	2.7	2.0	12.7	17	92.85	1578.5	544	13056	2.902
	3.2	2.5	15.9	15	95.64	1434.6	480	11520	2.989
	3.7	3.0	19.1	12	98.43	1181.2	384	9216	3.076
	4.2	3.5	22.3	11	101.25	1113.8	352	8448	3.164
	4.7	4.0	25.6	10	104.04	1040.4	320	7680	3.251
Xci PLY (CLASS A) - 3/4" FT PLY	1.7	1.0	6.6	28	87.50	2450.00	896	17920*	2.734
	2.2	1.5	9.6	21	90.35	1897.35	672	13440*	2.823
	2.7	2.0	12.7	17	93.20	1584.40	544	13056	2.913
	3.2	2.5	15.9	15	95.75	1436.25	480	11520	2.992
	3.7	3.0	19.1	12	98.30	1179.60	384	9216	3.072
	4.2	3.5	22.3	11	101.15	1112.65	352	8448	3.161
	4.7	4.0	25.6	10	104.00	1040.00	320	7680	3.250

*Truck load quantity varies on gross weight of loaded truck.