



H-Shield

Packaging & Weight Chart

SIZE	LTTR	PCS/PL	*DP PCS/PL	LBS/4X8 PC	LBS/4X4 PL	4X4 SF/PL	*DP 4X4 LBS PL 4X8 LBS PL	*DP 4X4 SF PL 4X8 SF PL	SF/48' TRL	WEIGHT PER SF
0.5		96	192	5.18	248.54	1536	497.09	3072	73728	0.16
1.0	5.7	48	96	7.71	185.06	768	370.13	1536	36864	0.24
1.1	6.3	43	86	8.22	176.69	688	353.37	1376	33024	0.26
1.2	6.8	40	80	8.73	174.50	640	349.00	1280	30720	0.27
1.3	7.4	36	72	9.23	166.16	576	332.32	1152	27648	0.29
1.4	8.0	34	68	9.74	165.55	544	331.09	1088	26112	0.30
1.5	8.6	32	64	10.25	163.92	512	327.84	1024	24576	0.32
1.6	9.1	30	60	10.75	161.27	480	322.53	960	23040	0.34
1.7	9.7	28	56	11.26	157.61	448	315.22	896	21504	0.35
1.75	10.0	27	54	11.52	155.52	432	311.04	864	20736	0.36
1.8	10.3	26	52	11.77	152.95	416	305.89	832	19968	0.37
1.9	10.8	25	50	12.27	153.39	400	306.78	800	19200	0.38
2.0	11.4	24	48	12.78	153.34	384	306.67	768	18432	0.40
2.1	12.0	22	44	13.29	146.14	352	292.27	704	16896	0.42
2.2	12.6	21	42	13.79	144.81	336	289.61	672	16128	0.43
2.3	13.2	20	40	14.30	142.98	320	285.96	640	15360	0.45
2.4	13.8	20	40	14.81	148.05	320	296.10	640	15360	0.46
2.5	14.4	19	38	15.31	145.45	304	290.91	608	14592	0.48
2.6	15.0	18	36	15.82	142.36	288	284.72	576	13824	0.49
2.7	15.6	17	34	16.33	138.76	272	277.53	544	13056	0.51
2.8	16.2	17	34	16.83	143.06	272	286.13	544	13056	0.53
2.9	16.8	16	32	17.34	138.70	256	277.41	512	12288	0.54
3.0	17.4	16	32	17.85	142.76	256	285.52	512	12288	0.56
3.1	18.0	15	30	18.35	137.63	240	275.27	480	11520	0.57
3.2	18.6	15	30	18.86	141.44	240	282.87	480	11520	0.59
3.3	19.2	14	28	19.37	135.56	224	271.11	448	10752	0.61
3.4	19.9	14	28	19.87	139.10	224	278.19	448	10752	0.62
3.5	20.5	13	26	20.38	132.46	208	264.91	416	9984	0.64
3.6	21.1	13	26	20.89	135.75	208	271.51	416	9984	0.65
3.7	21.7	12	24	21.39	128.35	192	256.69	384	9216	0.67
3.8	22.3	12	24	21.90	131.39	192	262.78	384	9216	0.68
3.9	23.0	12	24	22.41	134.43	192	268.86	384	9216	0.70
4.0	23.6	12	24	22.91	137.47	192	274.93	384	9216	0.72
4.1	24.2	11	22	23.42	128.80	176	257.60	352	8448	0.73
4.2	24.9	11	22	23.93	131.59	176	263.18	352	8448	0.75
4.3	25.5	11	22	24.43	134.37	176	268.74	352	8448	0.76
4.4	26.1	10	20	24.94	124.69	160	249.38	320	7680	0.78
4.5	26.8	10	20	25.45	127.23	160	254.45	320	7680	0.80

To achieve optimal thermal performance Hunter Panels recommends installation of a multi-layered system with staggered joints.

*DP: Double Packs consist of 2 stacks of 4'x4' polyiso, side by side, shrink wrapped and bagged together to ship as a 4x8 unit. In an effort to speed up unloading of trucks, staging of jobs and crane usage - the double packs are a preferred packaging option. 4'x4' polyiso is now available in single and double packs.