



# H-Shield CG

## Packaging & Weight Chart

SIZE	LTTR	PCS/PL	LBS/4X8 PC	LBS/4X4 PL	4X4 SF/PL	LBS/4X8 PL	4X8 SF/PL	SF/48' TRL	WEIGHT PER SF
0.5		96	9.45	453.60	1536	907.20	3072	73728	0.30
1.0	5.7	48	12.24	293.74	768	587.47	1536	36864	0.38
1.1	6.3	43	12.81	275.42	688	550.83	1376	33024	0.40
1.2	6.8	40	13.35	266.96	640	533.92	1280	30720	0.42
1.3	7.4	36	13.92	250.54	576	501.08	1152	27648	0.43
1.4	8.0	34	14.49	246.33	544	492.66	1088	26112	0.45
1.5	8.6	32	15.03	240.45	512	480.90	1024	24576	0.47
1.6	9.1	30	15.60	233.99	480	467.97	960	23040	0.49
1.7	9.7	28	16.17	226.38	448	452.76	896	21504	0.51
1.75	10.0	27	16.44	221.94	432	443.88	864	20736	0.51
1.8	10.3	26	16.71	217.20	416	434.41	832	19968	0.52
1.9	10.8	25	17.28	215.99	400	431.98	800	19200	0.54
2.0	11.4	24	17.85	214.20	384	428.40	768	18432	0.56
2.1	12.0	22	18.39	202.27	352	404.54	704	16896	0.57
2.2	12.6	21	18.96	199.07	336	398.14	672	16128	0.59
2.3	13.2	20	19.53	195.30	320	390.60	640	15360	0.61
2.4	13.8	20	20.07	200.68	320	401.36	640	15360	0.63
2.5	14.4	19	20.64	196.07	304	392.14	608	14592	0.64
2.6	15.0	18	21.21	190.89	288	381.78	576	13824	0.66
2.7	15.6	17	21.75	184.86	272	369.72	544	13056	0.68
2.8	16.2	17	22.32	189.71	272	379.42	544	13056	0.70
2.9	16.8	16	22.89	183.12	256	366.24	512	12288	0.72
3.0	17.4	16	23.43	187.42	256	374.85	512	12288	0.73
3.1	18.0	15	24.00	179.99	240	359.99	480	11520	0.75
3.2	18.6	15	24.57	184.28	240	368.55	480	11520	0.77
3.3	19.2	14	25.11	175.76	224	351.51	448	10752	0.78
3.4	19.9	14	25.68	179.75	224	359.51	448	10752	0.80
3.5	20.5	13	26.25	170.63	208	341.25	416	9984	0.82
3.6	21.1	13	26.79	174.12	208	348.24	416	9984	0.84
3.7	21.7	12	27.36	164.15	192	328.31	384	9216	0.85
3.8	22.3	12	27.93	167.58	192	335.16	384	9216	0.87
3.9	23.0	12	28.47	170.81	192	341.62	384	9216	0.89
4.0	23.6	12	29.04	174.23	192	348.47	384	9216	0.91
4.1	24.2	11	29.61	162.86	176	325.71	352	8448	0.93
4.2	24.9	11	30.18	165.99	176	331.98	352	8448	0.94
4.3	25.5	11	30.72	168.95	176	337.91	352	8448	0.96
4.4	26.1	10	31.29	156.45	160	312.90	320	7680	0.98
4.5	26.8	10	31.83	159.14	160	318.28	320	7680	0.99

**To achieve optimal thermal performance Hunter Panels recommends installation of a multi-layered system with staggered joints.**

**HUNTER**  
*Energy Smart Polyiso*

**888-746-1114 • WWW.HUNTERPANELS.COM**