



The Hunter Panels SIP WD Fastener is intended to mechanically attach Cool-Vent and H-Shield NB to wood substrates. The Hunter Panels SIP WD Fastener has the following features:

- FM approved—plates not required
- Pull-out values for plywood
- Star/spider head eliminates need for washer and offers dramatically increased pull-out value
- Multiple bits included in each pail
- 100% American made
- Fast, one-step installation
- No pre-drilling

| Test Description | Typical Value |
|------------------------|---------------|
| Pull-through (lbs) | 630 |
| Pull-out (lbs): | |
| 1/2" plywood | 442 |
| 5/8" plywood | 459 |
| 3/4" plywood | 710 |
| Douglas Fir (1" pen.) | 768 |

Fasteners should never be struck with a hammer during installation.

PHYSICAL DATA CHART

| | |
|-----------------|---|
| Head Diameter | .625" |
| Thread Diameter | .240" |
| Shank Diameter | .190" |
| Fastener Length | 3.5", 4", 4.5", 5", 5.5", 6", 6.5", 7", 7.5", 8", 9", 10", 11", 12", 13", 14" |

- Fastener thread shall extend a minimum of 3/4" beyond the underside of OSB/plywood decks.
- Fastener thread shall penetrate a minimum of 1" into plank/T&G decks.
- Values are per FM 4470

