

INCREASE YOUR CONTINUOUS INSULATION OPTIONS WITH XCI 286

Hunter Xci 286 is two-sided, reflective foil and white foil to meet your design criteria.

THE PRODUCT

- Manufactured with NexGen Chemistry: Zero Ozone Depleting Potential (ODP); Contains no CFCs, HCFCs or HFCs; Virtually zero Global Warming Potential (GWP). Use of Xci products helps reduce the carbon footprint of buildings.
- May be left exposed on the interior of buildings with no additional thermal barrier required
- Aesthetic exposure options
 - Either side of the product is approved to be left exposed, reflective foil or white foil
 - Matching white foil tape available for joint treatment
- Potential for added R-value if reflective foil face is installed toward the wall cavity per ASHRAE Fundamental Handbook
- Polyiso foam core high R-value in thin profile
- Available Grade 2 (20 psi) or Grade 3 (25 psi)
- Available in 4' x 8' or custom sizes, from 1" 3.5" with R-values from 6.3 22.0
- Pressure washable 15 mil facer

APPLICATIONS

 Provides exposed interior continuous insulation in commercial and residential applications such as: metal buildings, attic knee walls and floors, crawl spaces, parking garages, basements, industrial and agricultural buildings.

THE APPROVALS

- NFPA 286 passed for exposed interior ceiling or wall applications
- Facilitates compliance with the most current ASHRAE 90.1, IECC, IBC and IRC standards
- ASTM D1037 for Impact Resistance Test passed
- Provides exterior sheathing options in tested NFPA 285 wall assemblies.
 Contact Hunter Xci for details.

SALES BENEFITS

- Reduced stocking inventory one product serves multiple functions resulting in fewer SKU's
- Single Source Responsibility trucks can be filled with other Xci polyiso products
- Multiple Manufacturing Facilities







For more information and samples, contact Hunter Panels or visit www.hunterpanels.com.

CONTINUOUS INSULATION

15 Franklin Street = Portland, Maine 04101 = 888.746.1114 = info@hpanels.com = www.hunterpanels.com