



HUNTER

# PACKAGING AND WEIGHT

	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
<b>Xci FOIL</b>	1.0	6.5	48	6.37	305.66	1536	36864	0.200
	1.5	10.0	32	9.02	288.77	1024	24576	0.280
	2.0	13.3	24	11.71	281.09	768	18432	0.370
	2.5	17.0	19	14.37	272.99	608	14592	0.450
	3.0	20.3	16	17.02	272.38	512	12288	0.530
	3.5	24.0	13	19.71	256.26	416	9984	0.620
	4.0	27.0	12	22.37	268.42	384	9216	0.700
<b>Xci FOIL CLASS A</b>	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
<b>Xci FOIL CLASS A PLUS</b>	1.0	6.5	48	7.60	364.80	1536	36864	0.238
	1.6	10.4	30	11.40	342.00	960	23040	0.356
	2.0	13.3	24	14.00	336.00	768	18432	0.436
	2.5	17.0	19	17.20	326.80	608	14592	0.538
	3.0	20.3	16	20.40	326.40	512	12288	0.638
<b>Xci 286</b>	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
<b>Xci CG</b>	1.0	6.0	48	12.24	587.47	1536	36864	0.380
	1.5	9.0	32	15.03	480.90	1024	24576	0.470
	2.0	12.1	24	17.85	428.40	768	18432	0.560
	2.5	15.3	19	20.64	392.14	608	14592	0.640
	3.0	18.5	16	23.43	374.85	512	12288	0.730
	3.5	21.7	13	26.25	341.25	416	9984	0.820
	4.0	25.0	12	29.04	348.47	384	9216	0.910

	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
<b>Xci CG CLASS A</b>	1.0	6.0	48	12.50	600.00	1536	36864	0.391
	1.5	9.0	32	15.35	491.20	1024	24576	0.480
	2.0	12.1	24	18.20	436.80	768	18432	0.569
	2.5	15.3	19	20.75	394.25	608	14592	0.648
	3.0	18.5	16	23.30	372.80	512	12288	0.728
	3.5	21.7	13	26.15	339.95	416	9984	0.817
	4.0	25.0	12	29.00	348.00	384	9216	0.906
<b>Xci CONCAST</b>	1.0	6.5	48	6.00	312.00	1536	36864	0.190
	1.5	10.0	32	8.00	279.00	1024	24576	0.250
	2.0	13.3	24	11.00	270.00	768	18432	0.340
	2.5	17.0	19	13.30	252.70	608	14592	0.420
	3.0	20.3	16	16.00	255.00	512	12288	0.500
	3.5	24.0	13	16.87	219.30	416	9984	0.527

	SIZE	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
<b>Xci NB - 7/16" OSB</b>	1.5	1.0	6.6	32	60.24	1927.7	1024	24576	1.880
	2.0	1.5	9.6	24	63.03	1512.7	768	18432	1.970
	2.5	2.0	12.7	19	65.85	1251.2	608	14592	2.060
	3.0	2.5	15.9	16	68.64	1098.2	512	12288	2.140
	3.5	3.0	19.1	13	71.43	928.6	416	9984	2.230
	4.0	3.5	22.3	12	74.25	891.0	384	9216	2.320
	4.5	4.0	25.6	10	77.04	770.4	320	7680	2.410
<b>Xci NB - 5/8" OSB</b>	1.6	1.0	6.6	30	77.24	2317.2	960	23040	2.411
	2.1	1.5	9.6	22	80.03	1760.7	704	16896	2.501
	2.6	2.0	12.7	18	82.85	1491.3	576	13824	2.591
	3.1	2.5	15.9	15	85.64	1284.6	480	11520	2.671
	3.6	3.0	19.1	13	88.48	1150.2	416	9984	2.761
	4.1	3.5	22.3	11	91.25	1003.8	352	8448	2.851
<b>Xci NB - 5/8" PLY</b>	1.6	1.0	6.8	30	67.24	2017.2	960	23040	2.101
	2.1	1.5	9.8	22	70.03	1540.7	704	16896	2.188
	2.6	2.0	12.9	18	72.85	1311.3	576	13824	2.277
	3.1	2.5	16.1	15	75.64	1134.6	480	11520	2.364
	3.6	3.0	19.3	13	78.43	1019.6	416	9984	2.451
	4.1	3.5	22.5	11	81.25	893.8	352	8448	2.539
	4.6	4.0	25.8	10	84.04	940.4	320	7680	2.626
<b>Xci NB - 3/4" PLY</b>	1.7	1.0	7.0	28	77.24	2162.7	896	17920*	2.411
	2.2	1.5	10.0	21	80.03	1680.6	672	16128	2.501
	2.7	2.0	13.1	17	82.85	1408.5	544	13056	2.591
	3.2	2.5	16.3	15	85.64	1284.6	480	11520	2.671
	3.7	3.0	19.5	12	88.43	1061.2	384	9216	2.761
	4.2	3.5	22.5	11	91.25	1003.8	352	8448	2.851
	4.7	4.0	26.0	10	94.04	940.4	320	7680	2.941
<b>Xci PLY - 5/8" FT PLY</b>	1.6	1.0	6.8	30	77.24	2317.2	960	19200*	2.411
	2.1	1.5	9.8	22	80.03	1760.7	704	16896	2.501
	2.6	2.0	12.9	18	82.85	1491.3	576	13824	2.591
	3.1	2.5	16.1	15	85.64	1284.6	480	11520	2.671
	3.6	3.0	19.3	13	88.43	1149.6	416	9984	2.761
	4.1	3.5	22.5	11	91.25	1003.8	352	8448	2.851
	4.6	4.0	25.8	10	94.04	940.4	320	7680	2.941

	SIZE	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
<b>Xci PLY CLASS A - 5/8" FT PLY</b>	1.6	1.0	6.8	30	77.50	2325.00	960	19200*	2.422
	2.1	1.5	9.8	22	80.35	1767.70	704	16896	2.511
	2.6	2.0	12.9	18	83.20	1497.60	576	13824	2.600
	3.1	2.5	16.1	15	85.75	1286.25	480	11520	2.679
	3.6	3.0	19.3	13	88.30	1147.90	416	9984	2.759
	4.1	3.5	22.5	11	91.15	1002.65	352	8448	2.848
	4.6	4.0	25.8	10	94.00	940.00	320	7680	2.937
<b>Xci PLY - 3/4" FT PLY</b>	1.7	1.0	7.0	28	87.24	2442.7	896	17920*	2.726
	2.2	1.5	10.0	21	90.03	1890.6	672	13440*	2.813
	2.7	2.0	13.1	17	92.85	1578.5	544	13056	2.902
	3.2	2.5	16.3	15	95.64	1434.6	480	11520	2.989
	3.7	3.0	19.5	12	98.43	1181.2	384	9216	3.076
	4.2	3.5	22.7	11	101.25	1113.8	352	8448	3.164
	4.7	4.0	26.0	10	104.04	1040.4	320	7680	3.251
<b>Xci PLY CLASS A - 3/4" FT PLY</b>	1.7	1.0	7.0	28	87.50	2450.00	896	17920*	2.734
	2.2	1.5	10.0	21	90.35	1897.35	672	13440*	2.823
	2.7	2.0	13.1	17	93.20	1584.40	544	13056	2.913
	3.2	2.5	16.3	15	95.75	1436.25	480	11520	2.992
	3.7	3.0	19.5	12	98.30	1179.60	384	9216	3.072
	4.2	3.5	22.7	11	101.15	1112.65	352	8448	3.161
	4.7	4.0	26.0	10	104.00	1040.00	320	7680	3.250

\*Truck load quantity varies on gross weight of loaded truck.